



# SAMMONS EQUIPMENT MANUFACTURING CORPORATION

Shammi Industries

## Universal angle cabinets, heavy duty, insulated & non-insulated, aluminum

390-A Meyer Circle, Corona, California 92879-1078

Phone (951) 340-3419

Fax (951) 340-2716

- Ideal for schools, institutions, hotels & hospitals.
- Easily accommodates various sizes of pans & trays from 16" to 21" in width up to 26" long, all in one unit.
- Choice of insulated or non-insulated units.



These cabinets use universal angle which can hold 18"x26" bun pans, 14"x18" trays, 12"x20" steam pans, gastronorm (GN 2/1 and GN 1/1) pans, 10"x20" or 20"x22" roasting and baking pans and various other sizes. These angles are normally placed on 4 1/2" centers and are adjustable on 1 1/2" centers.




Insulated Model 9152-IN-13  
With Optional Wrap Around Bumper



Non-Insulated Model 9150-12

**Specifications:** Hi-tensile aluminum construction. Uprights are 2"x1"x1/4" extruded channels and slides are 0.105" thick step angle type adjustable on 1 1/2" centers (fixed optional). Doors are removable and use heavy duty stainless steel hinges and latches. 5" deluxe swivel casters are standard. Non insulated models use fixed racks and 270° door swing and single wall construction with 0.080" thick sides, back, door and top and 0.190" thick deck. Insulated models use 0.063" thick double wall construction with fiberglass insulation and removable rack. Deck is heavy duty reinforced.



\*Adjustable on 1 1/2" centers

### UNIVERSAL STEP ANGLE SLIDE

### Universal Angle Slide Cabinets:

Type	Model Number	Tray Capacity (see note)	*Slide Spacing inches (mm)	No. of Slide Sets furn.	Overall Dimensions Inches (mm)			Weight Pounds (kg)
					Width	Depth	Height	
Non-Insulated	9150-11	11	4 1/2 (114)	11	26 (660)	31 (787)	59 1/2 (1511)	145 (66)
	9150-12	12	4 1/2 (114)	12	26 (660)	31 (787)	65 1/2 (1664)	155 (70)
	9150-13	13	4 1/2 (114)	13	26 (660)	31 (787)	70 (1778)	170 (77)
Insulated	9152-IN-6	6	4 1/2 (114)	5	29 (737)	35 1/2 (902)	42 (1067)	196 (89)
	9152-IN-10	10	4 1/2 (114)	9	29 (737)	35 1/2 (902)	60 (1524)	230 (104)
	9152-IN-13	13	4 1/2 (114)	12	29 (737)	35 1/2 (902)	72 (1829)	280 (127)

\*Adjustable on 1 1/2" (38mm) centers.

**Note:** Capacity shown is for 18"x26" bun pans. Each set of slides can carry one (1) each 18"x26" or 20"x22" bun pan or 530mmx650mm gastronorm (GN 2/1) pan or can carry two (2) each 14"x18" trays, 12"x20" U.S. (or 325mmx530mm) GN 1/1 gastronorm steam pans or 10"x20" pans.

#### Correctional Package:

These cabinets are also available with correctional package which includes 3 sets of non-removable hinges, fixed slides, lockable 24" long 12 GA. S/S vertical security padlock hasp, tamperproof screws, perimeter bumper and 6" balloon casters. Consult factory.

#### Options:

1. Wheel brakes
2. Corner bumpers
3. Full perimeter non-marking wrap around bumper.
4. 6" polyurethane casters.
5. Floor lock (cart stop) device.
6. 3 sided top rail for transport of light objects.
7. Lockable door latch.
8. Non-removable door.
9. Pull handles.
10. Removable rack for non-insulated models. (Std. on insulated models).
11. 6" balloon casters.
12. Correctional package (consult factory)
13. Dutch doors.
14. Stainless steel construction.

Better food service equipment — standard models and custom designs.