

## Insulated stainless steel tray delivery cart for insulated trays for correctional facilities

390-A Meyer Circle • Corona, CA 92879-1078 • Phone (951) 340-3419 • Fax (951) 340-2716 • www.sammonsequipment.com

These heavy duty carts provide an effective and efficient delivery of stacked insulated trays in correctional or other heavy institutional food facilities. 14 ga reinforced deck & 12 ga. s/s hinges are standard. All models use 1½" fiberglass insulation, 22 ga. inner & 20 ga. outer (18 ga. optional). Correctional package is also available. Consult factory.

- Fully insulated non-heated s/s cabinets for transporting stacked insulated trays.
- Choice of single, double or triple door cabinets.
- 6" casters (5" for single section cabinets), push handle & perimeter bumper are standard.
- Heavy duty reinforced correctional hinges.

(For 11"x 16"x 2¾" and 13⅞"x 15½"x 2½" thk. stacked insulated trays)

| Model Number       | Tray Size (Inches)                   | Type of Door                             | Tray Capacity | O.A. Dimensions (Inches) |     |     | Weight (Pounds) |     |
|--------------------|--------------------------------------|--|---------------|--------------------------|-----|-----|-----------------|-----|
|                    |                                      |  |               | D                        | W   | H   |                 |     |
| 2151-HD-1116-48    | 11x16x2¼<br>(T-140)<br>SEE<br>NOTE 2 | Single                                   | 48            | 41½                      | 31½ | 60½ | 380             |     |
| 2151-HD-1116-30    |                                      | Single                                   | 30            | 41½                      | 31½ | 43  | 363             |     |
| 2151-HD-2-1116-52  |                                      | Double                                   | 52            | 31½                      | 48½ | 52¾ | 405             |     |
| 2151-HD-2-1116-60  |                                      | Double                                   | 60            | 31½                      | 48½ | 58¾ | 430             |     |
| 2151-HD-2-1116-68  |                                      | Double                                   | 68            | 31½                      | 48½ | 64¾ | 450             |     |
| 2151-HD-3-1116-78  |                                      | Triple                                   | 78            | 31½                      | 69¾ | 52¾ | 490             |     |
| 2151-HD-3-1116-90  |                                      | Triple                                   | 90            | 31½                      | 69¾ | 60  | 580             |     |
| 2151-HD-3-1116-102 |                                      | Triple                                   | 102           | 31½                      | 69¾ | 64¾ | 596             |     |
| 2151-HD-1315-30    |                                      | 13⅞x15½x2½<br>(ALLADIN)<br>SEE<br>NOTE 3 | Single        | 30                       | 38⅞ | 29  | 60½             | 375 |
| 2151-HD-1315-16    |                                      |  | Single        | 16                       | 38⅞ | 29  | 43              | 350 |
| 2151-HD-2-1315-56  | Double                               |  | 56            | 37¼                      | 48½ | 52¾ | 390             |     |
| 2151-HD-2-1315-64  | Double                               |  | 64            | 37¼                      | 48½ | 58¾ | 460             |     |
| 2151-HD-3-1315-84  | Triple                               |  | 84            | 37¼                      | 69¾ | 52¾ | 625             |     |
| 2151-HD-3-1315-96  | Triple                               |  | 96            | 37¼                      | 69¾ | 60  | 650             |     |



**2151-HD-2-1116-68**  
(with correctional package)

**NOTE 1:** These cabinets are also available with heating unit and for other tray sizes. Consult factory.

**NOTE 2:** These models for 11"x16"x2¼" trays will also carry Duralux T-240 (11¼"x15½"x2 2/5" thk), Incellator #2 & 3 (10"x16"x2.15" or 2.85" thk), Plastocon (10¾"x14½"x2½" or 3¼" thk) and Rock (9½"x14¼"x1⅞" thk) trays. Capacity will vary.

**NOTE 3:** Double & triple door models for 13⅞"x15½"x2½" will NOT go thru a standard 33"W door. Please make sure that your hallway door openings are larger than 38" for these carts. These models will also carry design specialty T-340 (13⅞"x15⅞"x2 9/16" thk) and Plastocon (Insulator & Supermax 13.6"x15"x2.86" thk) trays. Capacity will vary.

**NOTE 4:** Sample tray is required with order for proper sizing.

**NOTE 5:** These cabinets are also available as heated cabinets. Aluminum construction is also available. Consult factory.

**Options:**

Correctional package

18 ga. Exterior

Top mounted latch

6" Balloon casters upgrade

8" Balloon casters upgrade

8" Polyurethane casters upgrade



Better food service equipment – standard models and custom designs.

B-26A