

- Extremely versatile for small loads around the kitchen and serving area.
- Choice of insulated or non-insulated models & type of slides.
- Choice of aluminum or stainless steel exterior for insulated models.

These small cabinets provide excellent mobility for small numbers of 18"x26" bun pans or 12"x20" steam pans / gastronorm pans. All cabinets roll easily on 5" deluxe casters. Insulated cabinets are furnished with fiberglass insulation and have removable aluminum racks. Non-insulated models have fixed racks. Cabinets can be placed next to a counter or under counter depending upon the height. The heating module is completely removable for easily cleaning without the use of tools.



Insulated Model (channel Slide)  
9292-HIN-1208 (For 12"x20"x2 1/2" Steam pans)



Insulated Model (Angle Slide)  
9282-HIN-1808



Non-Insulated Model  
(Extruded Slides)  
9250-H-1810

**Thermometer:** Through the door type with dial on the outside for easy reading of the temperature without opening the door.

**Heating Unit (HE-1600):** Easy lift out type, 1600W heating coil, 1675W total, 120 VAC, 60 Hz, single phase, furnished with 15 amps 3 prong Nema 5-15P grounding plug. Heating unit comes standard with 75 watts blower, an electric hand set 10 hour timer with an off-on switch, thermostat and pilot lights for power and heating. Unit has over 4 quarts of water reservoir with an adjustable opening cover. Heating coil and blower are thermally protected.

**Note:** for use in Canada, HE-1600 is furnished with 20 amps cord & plug. Consult factory.

### Small Heated Cabinets

Type	Model No.		Type of Slide	Pan Size (inches)	Pan Capacity	Pan Spacing (inches)	O.A. Dimensions (inches)			Shipping Weight (Pounds)	
	Aluminum	Stainless Steel					Width	Depth	Height	Alum.	S/S
INSULATED	9292-HIN-1208	2292-HIN-1208	Channel	*12x20	8	2 3/4	20 9/16	32 7/8	42	90	185
	9282-HIN-1808	2282-HIN-1808	Angle	18x26	8	3	26	35 1/2	42	96	198
	9272-HIN-1816	2272-HIN-1807	Corrugated	18x26	16	1 1/2	26	35 1/2	42	100	205
	9252-HIN-1816	2252-HIN-1816	Extruded	18x26	16	1 1/2	26	35 1/2	42	102	208
	9232-HIN-1805	2232-HIN-1805	Universal Angle	18x26 12x20	5 10	4 1/2	29	35 1/2	42	110	230
NON-INSULATED	9250-H-1810	—	Extruded	18x26	10	1 1/2	22	30 1/8	33 3/8	65	—
	9280-H-1805	2280-H-1805	Angle	18x26	5	3	22	30 1/8	33 3/8	60	130
	9280-H-1807	2280-H-1807	Angle	18x26	7	3	22	30 1/8	39 3/8	67	142
	9250-H-1208	—	Extruded	*12x20	8	3	25	30 1/8	33 3/8	69	—

#### Options:

- A. Four corner bumpers.
- B. Wrap around bumper.
- C. Wheel brakes (pair)
- D. Smaller dia. casters.
- E. Door tag holder
- F. 220/240V Application
- G. Lockable latch.
- H. Canadian application



LISTED



\*2 1/2" Deep pans.

**Better food service equipment — standard models and custom designs.**