

- Fully insulated heated cabinets for correctional facilities.
- Maintains prepared meals in compartment trays for prisoners at desired serving temperature.
- Heavy duty welded s/s construction.
- Offered in single, double and triple section style.
- Designed for 10 3/4" x 15" or 11 1/2" x 15 1/2" trays.  
(Other sizes available).

These hot cabinets are furnished with 1 1/2" fiberglass insulation and fixed (welded) slides. Cabinets roll easily on 6" casters. The bottom mounted heating unit is easily removable (non-removable optional) & provides the necessary gentle & forced air circulation with thermostatically controlled temperature.

Outer body, door & top are made of 20 ga. (18 ga. optional) polished stainless steel for strength & durability. Push handle, 14 ga. s/s reinforced deck, perimeter bumper, tamper resistant fasteners, heavy duty 12 ga. s/s reinforced correctional hinges & latches are standard.



**2285-HIN-2-1115-56**  
(shown with correctional package)



**HE-1600 Heating Unit:**

1600 W Heating coil, 1,675W total, 13.96 amps at 120 VAC 60 HZ single phase furnished with 15 amps, 8ft. long cord with 3 prong Nema 5-15 P grounding plug, off-on switch, 75W blower, thermostat and pilot lights. Unit has over 4 quarts capacity water reservoir. Blower and heating coils are thermally protected. Optional 220-240-V available. Optional HE-2000 heating unit with 2000W heating coil and 20 amps cord and 5-20P plug for \*20 amps service is also available (standard for triple door cabinet). Consult factory.

**THERMOMETER:** Through the door type with dial on the outside for easy reading of temperature without opening the door.

\*For Canadian application HE-2000 and HE-1600 are furnished with 30 amps/20amps cord and plug respectively.



**2285-HIN-3-1115-96**  
(shown with correctional package)

Model Number	Tray Spacing (Inches)	Type of Door	**Tray Capacity	O.A. Dimensions (Inches)			Weight (Pounds)
				D	W	H	
2285-HIN-1115-20	3	Single	20	31 1/2	26	50 3/4	210
2285-HIN-1115-30	3	Single	30	31 1/2	26	65 3/4	240
2285-HIN-2-1115-40	3	Double	40	31 1/2	48 1/2	52 1/2	300
2285-HIN-2-1115-56	3	Double	56	31 1/2	48 1/2	64 3/8	380
2285-HIN-3-1115-72	3	Triple	72	31 1/2	69 1/2	52 3/8	490
2285-HIN-3-1115-96	3	Triple	96	31 1/2	69 1/2	64 3/8	540

\*\* Cabinets will also accommodate 14 1/2" x 7" trays. Capacity will be 1 1/2 time the capacity shown. Cabinets are also available for 14" x 18" and 15" x 20" trays and for other sizes. These cabinets are also available without heating unit. Consult factory.

**ADDITIONAL CORRECTIONAL PACKAGE (OPTIONAL)**

1. Non-removable heating unit (in lieu of removable)
2. Heavy duty side/top mounted security lockable latch
3. 18 ga. s/s exterior
4. 6" balloon casters (in lieu of std 6")
5. Extra set of hinges (3 sets in lieu of 2 sets) for each door

*Better food service equipment — standard models and custom designs.*