

Separate hot / ambient cabinet sections for prisoners trays for correctional facilities

390-A Meyer Circle, Corona, California 92879-1078

Phone (951) 340-3419

Fax (951) 340-2716

- Fully insulated with separate sections for hot and cold trays.
- Bottom mounted heating unit with 15 amp cord & Nema 5-15 plug.
- 20 Ga. S/S exterior (18 GA optional).
- Heavy duty welded s/s construction.
- 6" x 2" poly casters, push handle & wrap around bumper are standard.

These hot cabinets are furnished with fiberglass insulation and have separate hot section & ambient section for trays. Cabinets roll easily on 6" casters. The bottom mounted heating unit is easily removable (non-removable optional) & provides the necessary gentle & forced air circulation with thermostatically controlled temperature.

Outer body, door & top are made of 20 GA. (18 GA. optional) polished stainless steel for strength & durability. Push handle, perimeter bumper, tamper resistant fasteners, 14 GA. s/s deck and heavy duty reinforced correctional hinges & latches are standard.



2289-2015-HIN-40
(with optional correctional package)

HE-1600 Heating Unit:

1600 W Heating coil, 1,675W total, 13.96 amps at 120 VAC 60 HZ single phase furnished with 15 amps, 8ft. long cord with 3 prong Nema 5-15 P grounding plug, off-on switch, 75W blower, thermostat and pilot lights. Unit has over 4 quarts capacity water reservoir. Blower and heating coils are thermally protected. Optional 220-240-V available. Optional HE-2000 heating unit with 2000W heating coil and 20 amps cord and 5-20P plug for *20 amps service is also available. Consult factory.

THERMOMETER: Through the door type with dial on the outside for easy reading of temperature without opening the door.

*For Canadian application HE-2000 and HE-1600 are furnished with 30 amps/20amps cord and plug respectively.

Model Number	Section	No. of Doors	Tray Size (Inches)	Spacing (Inches)	Capacity	O.A. Dimensions (Inches)			Weight (Pounds)
						D	W	H	
2289-2-HIN-910-56	Hot	1	9 x 10½ x 2½	3	56	31½	66	64¾	588
	Ambient	1	9 x 10½ x 2½	3	56				
2289-2-HIN-1015-40	Hot	2	10¾ x 15 x 1¾	3	40	31½	74¾	52¾	598
	Ambient	1	18 x 26	4	6				
2289-2-HIN-1015-56	Hot	2	10¾ x 15 x 1¾	3	56	31½	71¾	64¾	586
	Ambient	1	15 x 20	4	6				
2289-2-HIN-0609-56	Hot	1	6¼ x 9 x 1¾	3	56	31½	74¾	64¾	640
	Ambient	2	10¾ x 15 x 1¾	3	56				



NOTE: Sample trays are required with order. Cabinets for other sizes are available. Check door clearance to ensure cabinet will go thru'.

ADDITIONAL CORRECTIONAL PACKAGE (OPTIONAL)

1. Non-removable heating unit (in lieu of removable)
2. Heavy duty side/top mounted security lockable latch
3. 18 ga. s/s exterior
4. 6" balloon casters (in lieu of std 6")
5. Extra set of hinges (3 sets in lieu of 2 sets) for each door

ADDITIONAL OPTIONS:

- A. Towing Hitch
- B. S/S Frame insert for chilled trays.
- C. Dolly for S/S insert for ambient trays

Better food service equipment — standard models and custom designs.