

- **Fully insulated hot s/s cabinets.**
- **Bottom mounted heating unit with 1600W heating.**
- **2 different styles offered. (Choice of trays on 3” centers or stacked)**
- **5” casters & perimeter bumper are standard.**
- **Heavy duty reinforced correctional hinges.**

These hot cabinets are furnished with 1 ½” fiberglass insulation and are offered in two styles, one with removable rack with fixed slides spaced on 3” centers and the other with removable flat square tubing shelves for stacking trays. Cabinets roll easily on 5” casters, 2 with brakes. **The bottom mounted heating unit** is easily removable (non-removable optional) & provides the necessary gentle & forced air circulation with thermostatically controlled temperature.

Outer body, door & top are made of 20 ga. (18 ga. optional) polished stainless steel for strength & durability. Inners are made of 22 ga. s/s. Perimeter bumper, tamper resistant fasteners, heavy duty reinforced correctional hinges, latches and through the door type dial thermometer are standard.

HE-1600 Heating Unit:

1600 W heating coil, 1,675W total, 13.96 amps at 120 VAC 60 HZ single phase furnished with 15 amps, 8ft. long cord with 3 prong Nema 5-15 P grounding plug, off-on switch, 75W blower, thermostat and pilot lights. Unit has over 4 quarts capacity water reservoir. Blower and heating coils are thermally protected. Optional 220-240V available.

Optional HE-2000 heating unit with 2000W heating coil and 20 amps cord and 5-20P plug for *20 amps service is also available. Consult factory.

*For Canadian application HE-2000 and HE-1600 are furnished with 30 amps/20amps cord and plug respectively.



STYLE “A”
2285-HIN-910-48
(slides on 3” centers)

STYLE “A”: Slides are spaced on 3” centers (Double rack in each section)

Model Number	Tray Size (Inches)	Tray Spacing (Inches)	Tray Capacity	O.A. Dimensions (Inches) D x W x H	Weight (Pounds)
2285-HIN-910-78	9 x 10½ x 2½	3	78	38⅞ x 31½ x 60½	480
2285-HIN-910-60	9 x 10½ x 2½	3	60	38⅞ x 31½ x 51½	458
2285-HIN-910-48	9 x 10½ x 2½	3	48	38⅞ x 31½ x 43	430
2285-HIN-0608-140	6⅝x8½x2⅝	3	104	38⅞ x 29 x 60½	468
2285-HIN-0608-80	6⅝x8½x2⅝	3	80	38⅞ x 29 x 51½	442
2285-HIN-0608-64	6⅝x8½x2⅝	3	64	38⅞ x 29 x 43	420

STYLE “B”: Trays are to be stacked. Cabinet furnished without slides, but supplied with removable tubular shelves for stacking trays.

Model Number	Tray Size (Inches)	Tray Spacing (Inches)	Tray Capacity	O.A. Dimensions (Inches) D x W x H	Weight (Pounds)
2285-HIN-ST-910-84	9 x 10½ x 2½	Stacked	84	38⅞ x 31½ x 60½	360
2285-HIN-ST-910-72	9 x 10½ x 2½	Stacked	72	38⅞ x 31½ x 51½	348
2285-HIN-ST-910-48	9 x 10½ x 2½	Stacked	48	38⅞ x 31½ x 43	320
2285-HIN-ST-0608-153	6⅝x8½x2⅝	Stacked	153	38⅞ x 29 x 60½	349
2285-HIN-ST-0608-117	6⅝x8½x2⅝	Stacked	117	38⅞ x 29 x 51½	328
2285-HIN-ST-0608-81	6⅝x8½x2⅝	Stacked	81	38⅞ x 29 x 43	310



STYLE “B”
2285-HIN-ST-0608-153

- NOTE 1:** Prices are based on a minimum quantity of 5 units. For quantities under 5, consult factory. These cabinets are also available without the heating unit and for other size trays. Consult factory.
- NOTE 2:** Sample tray is required with order for proper sizing. Aluminum construction is also available. Consult factory.

ADDITIONAL CORRECTIONAL PACKAGE (OPTIONAL)

1. Non-removable heating unit (in lieu of removable)
2. Heavy duty side/top mounted security lockable latch
3. Extra set of hinges (3 sets in lieu of 2) for each door
4. 18 ga. s/s exterior
5. 6” polyurethane or 6” balloon casters
6. 8” polyurethane or 8” balloon casters

