

Hot insulated double & triple door cabinets for compartment trays for correctional facilities with top mounted heating unit.

390-A Meyer Circle • Corona, CA 92879-1078 • Phone (951) 340-3419 • Fax (951) 340-2716 • www.sammonsequipment.com

- Fully insulated hot s/s cabinets.(Double or triple doors)
- Top mounted heating unit with 1600W heating & 15 amps cord & NEMA 5-15P plug for double door cabinets .2000W heating with 20 amps cord & NEMA 5-plug for 3 door cabinets.(optional for 2 door cabinets)
- Welded s/s rack & heavy duty correctional hinges.
- 6" x 2" swivel casters, 2 with brakes, push handle & perimeter bumper are standard.

These cabinets are furnished with 1½" fiberglass insulation and fixed (welded) slides. The top mounted heating unit is easily removable (non removable optional) & provides the necessary gentle & forced air circulation with thermostatically controlled temperature.

Outer body, door & top are made of 20 ga. (18 ga. optional) polished stainless steel for strength & durability. Push handle. 14 ga. s/s reinforced deck, perimeter bumper, trapper resistant fasteners, heavy duty latches and 12 ga. s/s reinforced correctional hinges are standard.

HET-1600 Heating unit:

1600W heating coil, 1,750w total, 14.58 amps to 120VAC 60HZ single phase furnished with 15 amps, 8ft. long cord with 3 prong Nema 5-15 grounding plug, switch off-on switch, two 75w blowers, thermostat, pilot lights and dial thermometer. Blower and heating coils are thermally protected. Optional 220-240-V available. Optional HET-2000 heating unit with 2000w heating coil, 2150W total, 17.92 amps and 20 amp cord, and 5 -20P plug for 20 amps service is also available (standard for triple door cabinet). Consult factory.



2286-HIN-2-1115-60
(with correctional package)



A. For 10¾" x 15" or 11½" x 15½" compartment trays

Model Number	Tray Spacing (Inches)	Type of Door	**Tray Capacity	O.A. Dimensions (Inches)			Weight (Pounds)
				D	W	H	
2286-HIN-2-1115-52	3	Double	52	31½	48½	63¾	340
2286-HIN-2-1115-40	3	Double	40	31½	48½	55¼	300
2286-HIN-2-1115-60	3	Double	60	31½	48½	71¾	420
2286-HIN-3-1115-72	3	Triple	72	31½	69½	55¼	490
2286-HIN-3-1115-90	3	Triple	90	31½	69½	71¾	540

**Cabinets will also accommodate 14½" x 7" trays. Capacity will be 1½ time the capacity shown. Cabinets are also available for 14" x 18" & 15" x 20" trays and for other sizes, consult factory. Sample trays are required with order. Also see notes 1,2,& 3 and options below.

B. (For 9" x 10" x 2½" & 6¾" x 8½" x 2½" compartment trays). (Double door cabinets, Double sets of rack in each section)

Model Number	Tray Size (Inches)	Tray Spacing (Inches)	Tray Capacity	O.A. Dimensions (Inches)			Weight (Pounds)
				D	W	H	
2286-HIN-4-910-112	9 x 10½ x 2½	3	112	31½	58¾	64¾	590
2286-HIN-4-910-96	9 x 10½ x 2½	3	96	31½	58¾	58¾	565
2286-HIN-4-910-80	9 x 10½ x 2½	3	80	31½	58¾	52¾	530
2286-HIN-4-0608-168	6¾x8½x2½	3	168	31½	57¼	64¾	570
2286-HIN-4-0608-144	6¾x8½x2½	3	144	31½	57¼	58¾	536
2286-HIN-4-0608-120	6¾x8½x2½	3	120	31½	57¼	52¾	510

NOTE 1: These cabinets are also available without the heating unit and for other size trays. Consult factory.

NOTE 2: These cabinets are also available without internal racks for stacking trays capacity will vary. Contact Factory

NOTE 3: Sample tray is required with order for proper sizing.

Options:

1. Correctional package
2. Lockable hasps
3. 18 ga. exterior

Options:

4. 6" balloon casters upgrade
5. 8" balloon casters upgrade
6. 8" polyurethane casters upgrade



2286-HIN-3-1115-90
(with correctional package)

