

390-A Meyer Circle, Corona, California 92879-1078

Phone (951) 340-3419

Fax (951) 340-2716

- **Ideal for storage of #10 and #5 cans.**
- **Self feeding – automatic stock rotation with rear loading.**
- **Shipped fully assembled. Sanitary and maintenance free.**
- **Optional front load/unload, first in/first out rotation available.**

These can racks use hi-tensile aluminum all welded construction. Uprights are heavy wall extruded tubing/channels horizontal frame uses 2 1/2"x1"x0.100" wall extruded t-bars and 1"x1 1/4" angle with 1" square tubing at front and back. Cross braces using square tubing are welded to uprights for tall stationary units to provide extra strength. Stationary units have adjustable feet. Mobile units are provided with 5" casters.



Mobile Unit
Model 9560-M-72



Stationary Unit
Model 9560-216

Rear Loading, Self Feeding

Type of Unit	Model Number	Capacity		Type of Top	O.A. Dimensions (Inches)			Weight (Inches)
		#10 Cans	#5 Cans		W	D	H	
Stationary	9560-216	162	216	None	25 5/8	37 1/4	72	75
	9560-240	180	240	None	25 5/8	37 1/4	79 1/2	88
Mobile	9560-M-72	72	96	*Aluminum	25 5/8	37 1/4	40 3/8	64
	9560-M-54	54	72	*Aluminum	25 5/8	37 1/4	35	58

Options:

1. Removable solid shelf inserts (for smaller cans).
2. Stainless steel top (in lieu of aluminum) for mobile units.
3. All stainless construction.

Front Loading/Unloading, FIFO (first in, first out) Type

Type of Unit	Model Number	Capacity		Type of Top	O.A. Dimensions (Inches)			Weight (Inches)
		#10 Cans	#5 Cans		W	D	H	
Stationary	9560-285-FF	195	285	None	25 5/8	41 1/4	86 1/2	86
	9560-228-FF	156	228	None	25 5/8	41 1/4	69 1/2	75
	9560-171-FF	117	171	None	25 5/8	41 1/4	52 1/2	66

* For mobile units optional stainless steel top is available in lieu of aluminum top, add S130 to list price. All s/s construction is also available. Consult factory.

*Optional stainless steel top is available.

Better food service equipment — standard models and custom designs.