

**Extra heavy duty aluminum delivery cart  
for insulated trays for correctional facilities**

- Designed for thick insulated food trays.
- 6”x 2” polyurethane casters (2 swivel, 2 rigid).
- Extra heavy duty shelves.
- 1” dia. tubular handle.
- All welded aluminum construction.
- Three sided 1½” square tubing rail.

Model Number	Shelf Size (Inches)	Shelf Clearance (Inches)	Tray Size (Inches)	*Tray capacity bottom shelf	O.A. Dimensions (Inches) W x L x H	Weight (Pounds)
1940-EHD-2-2436	24 x 36	27	11 x 16 x 2¾	36	24½ x 36¼ x 45	125
1940-EHD-2-2452	24 x 52	27	11 x 16 x 2¾	54	24¼ x 52¼ x 45	145
1940-EHD-2-2950	29½ x 50	27	13¾ x 15¼ x 2½	60	29¾ x 50¼ x 45	160
1940-EHD-2-2964	29½ x 64	27	13¾ x 15¼ x 2½	80	29¾ x 64¼ x 45	184



1940-EHD-2-2436

\*Tray capacity shown is for bottom shelf. Top shelf will accommodate 2 to 3 beverage containers plus additional trays.

**NOTE:** Super heavy duty models are also available with additional reinforcement in top shelf, 1½” square tubing upright frame & 8”x 2” casters. Add “-SD” after model number.

**Options**

- A. 6 casters (4 swivel, 2 rigid) in lieu of 4 casters
- B. Vertical tray stops (2 on each end & up to 4 in the back) in bottom section
- C. Corner bumpers
- D. Brakes on 2 casters



**Heavy duty steam pan & tray storage dolly/  
rack/cart for correctional facilities**

- Heavy duty all welded aluminum construction.
- Available for 12”x 20” steam pans & 13¾x15¼x2½” insulated trays.
- Rolls on 6” heavy duty casters.

Model Number	Approx. Capacity	Tray/Pan Type	No. of Stacks	O.A. Dimensions D x W x H (Inches)	Weight (Pounds)
9130-200-1220	200	12”x 20”	2	30⅞ x 22 x 60	94
9130-160-1220	160	Steam Pans	2	30⅞ x 22 x 55	91
9130-40-1315	40	13¾”x15¼”x2½” Thick Insulated Trays	2	30⅞ x 22 x 61	96
9130-36-1315	36		2	30⅞ x 22 x 56	93
9130-64-1315	64		4	29½ x 36⅞ x 51	115
9130-96-1315	96		6	29½ x 54 x 51	120



9130-200-1220



9130-36-1315

**Note:** Capacity of steam pans is approx. Actual qty. may vary depending upon pan height. These units are also available for other insulated trays. Consult factory.

**Options**

- 1. 6” floor lock
- 2. 8” polyurethane casters (in lieu of 6”)

**Options**

- 3. S/S construction (add- “SS” after model #)
- 4. Corner bumpers