

aluminum

SAMMONS EQUIPMENT MFG. CORP. SHAMMI INDUSTRIES

SAMCO

Half size and undercounter deluxe

proofing cabinets non-insulated,

www.sammonsequipment.com

390-A Meyer Circle Corona, CA 92879-1078 Tel: (951) 340-3419 • Fax: (951) 340-2716

Furnished with PR-1600 proofing unit with 15 amps cord & NEMA 5-15P plug. 5" casters are standard. (except for undercounter cabinets which use 3" casters). Power Requirements: Total 1675 watts on 110-120 volts. 60 hz, Single Phase, A.C.

CATALOG PAGE C-36

Deluxe Proofing Cabinets (For 18" x 26" sheet pans)

Deluxe 1 tooling Cubinets (1 of 10 x 20 sheet pans)									
Туре	Size of Cabinet	Model Number	Pan Capacity (18''x26'')	Pan Spacing (Inches)	O.A W	(Inches)		Weight (Pounds)	List Price (See note)
Extruded	Undercounter	9251-DEP-1810-UC	10	1½	22	301/8	313/8	128	\$2,928
Sides	Half Size	9251-DEP-1818	18	11/2	22	301/8	453/8	150	3,353
*Angle	Undercounter	9281-DEP-1805-UC	5	*3	22	301/8	313/8	120	2,995
Ledge	Half Size	9281-DEP-1809	9	*3	22	301/8	453/8	150	3,380



9251-DEP-1818

Deluxe Proofing Cabinets (For 23" x 23" donut screens)

Tyma	Size of	Model Number	*Pan Capacity (23"x23")	*Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight	List Price
Туре	Cabinet				W	D	Н	(Pounds)	(See note)
Extruded	Under counter	9251-DEP-2305-UC	5	3	27	301/8	313/8	155	\$3,204
Sides	Half Size	9251-DEP-2307	7	3	27	301/8	393/8	165	\$3386
Sides	Full Size	9251-DEP-2317	17	3	27	301/8	693/8	180	\$3498

^{*} Slides are spaced on $1\frac{1}{2}$ " centers but the capacity is shown based on wire screens spaced on 3" centers.



9251-DEP-2305-UC

Deluxe Proofing Cabinets (Universal Angle Slide Type)

Type	Model Number	Pan Size (Inches)	Pan Capacity	Pan Spacing	O.A. Dimensions (Inches)			Weight (Pounds)	List Price
			Capacity	(Inches)	W	D	Н	(Fourkas)	(See note 3)
Undercounter	9231-DEP-UA-5-UC	Note 2	5 (Note 1)	3	291/2	331/8	313/8	245	\$3,198
Half Size	9231-DEP-UA-6	Note 2	6 (Note 1)	3	291/2	331/8	39	195	3,250
Haii Size	9231-DEP-UA-8	Note 2	8 (Note 1)	3	291/2	331/8	45	195	3,280

NOTE 1: Capacity shown is based on 3" spacing. Slides are adjustable on 11/2" centers.

NOTE 2: Each pair of slides can accommodate on 18"x 26" bun pan or one GN2/1 gastronorm pan or two 14"x 18" trays or one 23"x 23" screen or two 12"x 20" steam pans or two gastronorm GN1/1 pans.

NOTE: LEXAN® door is standard on all of these proofing cabinets. Solid door in lieu of LEXAN® door is available at no extra charge. These are also available in S/S construction. Replace first number "9" by number "2" in model number. Consult factory.



9231-DEP-UA-8

NOTE: All of these proofing cabinets are also available as heating & holding cabinets at no extra charge. Replace –"DEP" by –"H" in model number. These are also available as Hot/Proof combination cabinets. Replace "-DEP" by "-HP" in model number and add \$300 to list price. These will be furnished with 20 amp cord & 5-20P plug.

For other options, see table CC-1



SAMMONS EQUIPMENT MFG. CORP. **SHAMMI INDUSTRIES**

SAMCO www.sammonsequipment.com

390-A Meyer Circle Corona, CA 92879-1078 Tel: (951) 340-3419 • Fax: (951) 340-2716

TABLE CC-1 OPTIONS FOR PROOFER & HOT CABINETS

		LIST PRICE FOR		
		ALUMINUM MODELS	STAINLESS STEEL MODEL	
1.	Corner bumpers (set of 4)	\$149	\$164	
2.	Vertical leg bumpers (set of 4)	175	193	
3.	Wheel brakes (pair) for 5" or 6" casters	61	61	
4.	Wrap around bumper (single section cabinet)	269	305	
5.	Wrap around bumper (double section cabinet)	337	402	
	Floor lock (5")	188	249	
7.	Floor lock (6")	215	280	
	Floor lock (8")	292	355	
	Extra pair of universal angle slides	101	167	
	CASTERS UPGRADE (IN LIEU OF 5" STANDARD, SET OF 4)			
	A. 5" Polyurethane	119	119	
	B. 5" Balloon (decorative)	149	149	
	C. 6" Polyurethane (1,200# capacity)	184	184	
	D. 6" Heavy duty polyurethane (2,000# capacity)	280	280	
	E. 5" Hi-Temp	221	221	
	F. 6" Balloon	326	326	
	G. 8" Polyurethane	315	315	
	H. Stationary legs	280	280	
11	CASTERS UPGRADE (IN LIEU OF 6" STANDARD, SET OF 4)	200	200	
11.	A. 6" Balloon	236	236	
	B. 8" Balloon	390	390	
	C. 8" Polyurethane	249	249	
12	Swing door catch (for each door)	106	125	
	Door tag holder (for each door)	61	96	
	Lockable latch (for each door)	127	149	
	Top mounted latch (for each door)	244	299	
	Push handle (each)	167	215	
	Push handle (each) with 2 donut bumpers	215	272	
	Solid dutch doors (non-insulated) in lieu of single solid door	270	352	
	Solid dutch doors (insulated) in lieu of single solid door	342	559	
19.	Single LEXAN® door in lieu of single solid door	384	471	
20.	Dutch LEXAN® doors in lieu of single solid door	706	844	
	Dutch LEXAN doors in lieu of single LEXAN® door			
		279	355	
	*Single pass thru' door in the rear	546	697	
	*Dutch pass thru' doors in the rear	683	1,222	
	220v/240v application (in lieu of 120v)	348	348	
	Canadian application (in lieu of U.S.)	229	229	
	17 hour timer (in lieu of 10 hour)	145	145	
	HE-2000 (2,000w heating, 20 amps service unit) in lieu of HE-1600 (1,600w heating, 15 amps service unit)	184	184	
	Bail handles/pair/ side	145	201	
30.	Drain hole/section	132	132	
31.	Export crating	566	566	

^{*}FOR HOT INSULATED CABINETS WITH TOP MOUNTED HEATING UNITS ONLY.

NOTE: Most aluminum hot, proof & hot/proof cabinets are also available in s/s construction. Add 65% to list prices of aluminum models unless listed otherwise based on a minimum quantity of 5 units & an up charge of 20% to 80% may apply for quantities under 5. Consult factory.