



Hot universal angle slide cabinets, insulated & non-insulated

(Also See Note 3)

CATALOG PAGES C-7 & C-8

Furnished with HE-2000 heating unit with 20 amps cord & NEMA 5-20P plug. 5" casters are standard. Power Requirements: Total 2075 watts on 110-120 volts. 60 hz, Single Phase, A.C.

Aluminum Heated Cabinets with Universal Angle Slides (also see notes 3 & 4)

Type	Model Number (Also see note 3)	Tray Capacity (Note 1 & 2)	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)	List Price
				W	D	H		
Non-Insulated	9230-H-UA-9	9	4½	26	31	59½	202	\$3,656
	9230-H-UA-10	10	4½	26	31	65½	219	3,904
	9230-H-UA-11	11	4½	26	31	70	230	3,997
Insulated	9232-HIN-UA-9	9	4½	29½	36¼	60½	265	4,242
	*9232-HIN-DD-UA-12	12	4½	29½	36¼	72½	295	4,585



9230-H-UA-10

Stainless Steel Heated Cabinets with Universal Angle Slides (also see notes 3 & 4)

Type	Model Number (Also see note 3)	Tray Capacity (Note 1 & 2)	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)	List Price
				W	D	H		
Non-Insulated	2230-H-UA-9	9	4½	26	31	59½	252	P.O.R.
	2230-H-UA-11	11	4½	26	31	70	280	\$5,378
Insulated	2232-HIN-UA-9	9	4½	29½	36¼	60½	378	6,565
	2232-HIN-UA-12	12	4½	29½	36¼	72½	402	7,137
	*2232-HIN-DD-UA-12	12	4½	29½	36¼	72½	410	7,379



9232-HIN-DD-UA-12

*Furnished with dutch doors as standard on this model.

NOTE 1: Tray capacity is shown for 18"x 26" bun pans. Capacity for 12"x 20" steam pans/gastronom (GN1/1) pans (2½" or 4" high) or 14"x 18" trays is twice the number.

NOTE 2: Slides are adjustable on 1½" (38mm) centers. Each universal slide set can carry one (1) each 18"x 26" bun pan or 20"x 20" baking pan or 530mm x 650mm gastronorm (GN2/1) pan or 20"x 20" glass rack or two (2) each 12"x 20" steam pans or 325mm x 530mm gastronorm (GN1/1) pan or 14"x 18" trays or 10"x 20" roasting pans or 13⅝"x 20¾" school lunch baskets.

NOTE 3: These cabinets are also available as proofing cabinets in lieu of hot cabinets at no extra charge or as hot/proof combination cabinets at an additional price of \$385. Replace "-H" by "-P" in model number for proofing cabinets or replace "-H" by "-HP" for hot/proof combination cabinets.

NOTE 4: Hot insulated cabinets can also be furnished with 1600w heating unit (HE-1600) for 15 amps service instead of standard 2000w heating unit (HE-2000) at no extra charge. Consult factory. For other options, see Table CC-1.

Small heated cabinets insulated & non-insulated


Furnished with HE-1600 heating unit with 15 amps cord & NEMA 5-15P plug. 5" casters are standard. Power Requirements: Total 1675 watts on 110-120 volts. 60 hz, Single Phase, A.C.

Small Heated Cabinets CATALOG PAGE C-12

Type	Model Number		Type of Slide	Pan Size (Inches)	Pan Capacity	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)		List Price	
	Aluminum	Stainless Steel					W	D	H	Alum	SS	Alum	SS
Insulated	9292-HIN-1208	2292-HIN-1208	Channel	*12x20	8	2¾	20⅞	32⅞	43	190	228	P.O.R.	
	9282-HIN-1808	2282-HIN-1808	Angle	18x26	8	3	26	36¼	43	190	230		
	9252-HIN-1816	2252-HIN-1816	Extruded	18x26	16	1½	26	36¼	43	198	230		
	9232-HIN-1805	2232-HIN-1805	Universal Angle	18x26	5	4½	29	30%	43	237	305		
		12x20		10									
Non-Insulated	9250-H-1810	-	Extruded	18x26	10	1½	22	30%	33%	101	-	\$2,838	P.O.R.
	9280-H-1805	2280-H-1805	Angle	18x26	5	3	22	30%	33%	102	170	2,927	P.O.R.
	9280-H-1807	2280-H-1807	Angle	18x26	7	3	22	30%	39%	122	175	3,002	P.O.R.
	9250-H-1208	-	Extruded	*12x20	8	3	25	30%	33%	122	178	3,113	P.O.R.

*2½" Deep pans.

NOTE: These cabinets are also available as "proof" only or as hot/proof combination cabinets. See NOTE 3 above.



9292-HIN-1208



9250-H-1810



TABLE CC-1
OPTIONS FOR PROOFER & HOT CABINETS

Table with 3 columns: Item Description, ALUMINUM MODELS, and STAINLESS STEEL MODEL. Lists 31 items such as corner bumpers, casters, and heating units with their respective prices.

*FOR HOT INSULATED CABINETS WITH TOP MOUNTED HEATING UNITS ONLY.

NOTE: Most aluminum hot, proof & hot/proof cabinets are also available in s/s construction. Add 65% to list prices of aluminum models unless listed otherwise based on a minimum quantity of 5 units & an up charge of 20% to 80% may apply for quantities under 5. Consult factory.