



# Hot universal angle slide cabinets, insulated & non-insulated

(Also See Note 3)

CATALOG PAGES C-7 & C-8

Furnished with HE-2000 heating unit with 20 amps cord & NEMA 5-20P plug. 5" casters are standard. Power Requirements: Total 2075 watts on 110-120 volts. 60 hz, Single Phase, A.C.

## Aluminum Heated Cabinets with Universal Angle Slides (also see notes 3 & 4)

Type	Model Number (Also see note 3)	Tray Capacity (Note 1 & 2)	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)	List Price
				W	D	H		
Non-Insulated	9230-H-UA-9	9	4½	26	31	59½	202	\$3,656
	9230-H-UA-10	10	4½	26	31	65½	219	3,904
	9230-H-UA-11	11	4½	26	31	70	230	3,997
Insulated	9232-HIN-UA-9	9	4½	29½	36¼	60½	265	4,242
	*9232-HIN-DD-UA-12	12	4½	29½	36¼	72½	295	4,585



9230-H-UA-10

## Stainless Steel Heated Cabinets with Universal Angle Slides (also see notes 3 & 4)

Type	Model Number (Also see note 3)	Tray Capacity (Note 1 & 2)	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)	List Price
				W	D	H		
Non-Insulated	2230-H-UA-9	9	4½	26	31	59½	252	P.O.R.
	2230-H-UA-11	11	4½	26	31	70	280	\$5,378
Insulated	2232-HIN-UA-9	9	4½	29½	36¼	60½	378	6,565
	2232-HIN-UA-12	12	4½	29½	36¼	72½	402	7,137
	*2232-HIN-DD-UA-12	12	4½	29½	36¼	72½	410	7,379



9232-HIN-DD-UA-12

\*Furnished with dutch doors as standard on this model.

NOTE 1: Tray capacity is shown for 18"x 26" bun pans. Capacity for 12"x 20" steam pans/gastronom (GN1/1) pans (2½" or 4" high) or 14"x 18" trays is twice the number.

NOTE 2: Slides are adjustable on 1½" (38mm) centers. Each universal slide set can carry one (1) each 18"x 26" bun pan or 20"x 20" baking pan or 530mm x 650mm gastronorm (GN2/1) pan or 20"x 20" glass rack or two (2) each 12"x 20" steam pans or 325mm x 530mm gastronorm (GN1/1) pan or 14"x 18" trays or 10"x 20" roasting pans or 13¾"x 20¾" school lunch baskets.

NOTE 3: These cabinets are also available as proofing cabinets in lieu of hot cabinets at no extra charge or as hot/proof combination cabinets at an additional price of \$385. Replace "-H" by "-P" in model number for proofing cabinets or replace "-H" by "-HP" for hot/proof combination cabinets.

NOTE 4: Hot insulated cabinets can also be furnished with 1600w heating unit (HE-1600) for 15 amps service instead of standard 2000w heating unit (HE-2000) at no extra charge. Consult factory. For other options, see Table CC-1.

# Small heated cabinets insulated & non-insulated


Furnished with HE-1600 heating unit with 15 amps cord & NEMA 5-15P plug. 5" casters are standard. Power Requirements: Total 1675 watts on 110-120 volts. 60 hz, Single Phase, A.C.

## Small Heated Cabinets CATALOG PAGE C-12

Type	Model Number		Type of Slide	Pan Size (Inches)	Pan Capacity	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)		List Price	
	Aluminum	Stainless Steel					W	D	H	Alum	SS	Alum	SS
Insulated	9292-HIN-1208	2292-HIN-1208	Channel	*12x20	8	2¾	20⅞	32⅞	43	190	228	P.O.R.	
	9282-HIN-1808	2282-HIN-1808	Angle	18x26	8	3	26	36¼	43	190	230		
	9252-HIN-1816	2252-HIN-1816	Extruded	18x26	16	1½	26	36¼	43	198	230		
	9232-HIN-1805	2232-HIN-1805	Universal Angle	18x26	5	4½	29	30%	43	237	305		
		12x20		10									
Non-Insulated	9250-H-1810	-	Extruded	18x26	10	1½	22	30%	33%	101	-	\$2,838	P.O.R.
	9280-H-1805	2280-H-1805	Angle	18x26	5	3	22	30%	33%	102	170	2,927	P.O.R.
	9280-H-1807	2280-H-1807	Angle	18x26	7	3	22	30%	39%	122	175	3,002	P.O.R.
	9250-H-1208	-	Extruded	*12x20	8	3	25	30%	33%	122	178	3,113	P.O.R.

\*2½" Deep pans.

NOTE: These cabinets are also available as "proof" only or as hot/proof combination cabinets. See NOTE 3 above.



9292-HIN-1208



9250-H-1810



**TABLE CC-1  
OPTIONS FOR PROOFER & HOT CABINETS**

	LIST PRICE FOR	
	ALUMINUM MODELS	STAINLESS STEEL MODEL
1. Corner bumpers (set of 4)	\$149	\$164
2. Vertical leg bumpers (set of 4)	175	193
3. Wheel brakes (pair) for 5" or 6" casters	61	61
4. Wrap around bumper (single section cabinet)	269	305
5. Wrap around bumper (double section cabinet)	337	402
6. Floor lock (5")	188	249
7. Floor lock (6")	215	280
8. Floor lock (8")	292	355
9. Extra pair of universal angle slides	101	167
10. <u>CASTERS UPGRADE (IN LIEU OF 5" STANDARD, SET OF 4)</u>		
A. 5" Polyurethane	119	119
B. 5" Balloon (decorative)	149	149
C. 6" Polyurethane (1,200# capacity)	184	184
D. 6" Heavy duty polyurethane (2,000# capacity)	280	280
E. 5" Hi-Temp	221	221
F. 6" Balloon	326	326
G. 8" Polyurethane	315	315
H. Stationary legs	280	280
11. <u>CASTERS UPGRADE (IN LIEU OF 6" STANDARD, SET OF 4)</u>		
A. 6" Balloon	236	236
B. 8" Balloon	390	390
C. 8" Polyurethane	249	249
12. Swing door catch (for each door)	106	125
13. Door tag holder (for each door)	61	96
14. Lockable latch (for each door)	127	149
15. Top mounted latch (for each door)	244	299
16. Push handle (each)	167	215
17. Push handle (each) with 2 donut bumpers	215	272
18. Solid dutch doors (non-insulated) in lieu of single solid door	270	352
19. Solid dutch doors (insulated) in lieu of single solid door	342	559
20. Single LEXAN® door in lieu of single solid door	384	471
21. Dutch LEXAN® doors in lieu of single solid door	706	844
22. Dutch LEXAN® doors in lieu of single LEXAN® door	279	355
23. *Single pass thru' door in the rear	546	697
24. *Dutch pass thru' doors in the rear	683	1,222
25. 220v/240v application (in lieu of 120v)	348	348
26. Canadian application (in lieu of U.S.)	229	229
27. 17 hour timer (in lieu of 10 hour)	145	145
28. HE-2000 (2,000w heating, 20 amps service unit) in lieu of HE-1600 (1,600w heating, 15 amps service unit)	184	184
29. Bail handles/pair/ side	145	201
30. Drain hole/section	132	132
31. Export crating	566	566

\*FOR HOT INSULATED CABINETS WITH TOP MOUNTED HEATING UNITS ONLY.

**NOTE:** Most aluminum hot, proof & hot/proof cabinets are also available in s/s construction. Add 65% to list prices of aluminum models unless listed otherwise based on a minimum quantity of 5 units & an up charge of 20% to 80% may apply for quantities under 5. Consult factory.



Hot cabinets, non-insulated, aluminum & stainless steel

Furnished with HE-2000 heating unit with 20 amps cord & NEMA 5-20P plug. 5" casters are standard. Power Requirements: Total 2075 watts on 110-120 volts. 60 hz, Single Phase, A.C.

CATALOG PAGES C-5 & C-6

Aluminum Hot Non-Insulated Cabinets

Table with columns: Type, Model Number, Pan Size, Pan Spacing, Pan Capacity, O.A. Dimensions (W, D, H), Weight, List Price. Rows include Extruded Side Panel and Corrugated Sides models.



9250-H-1834

Stainless Steel Hot Non-Insulated Cabinets

Table with columns: Type of Slide, Model Number, Pan Size, Pan Spacing, Pan Capacity, O.A. Dimensions (W, D, H), Weight, List Price. Rows include Corrugated, Channel, and Angle Ledge models.



9270-H-1834

NOTE: Angle ledge cabinets are also available in spacing other than 3". Consult factory. For options, see Table CC-1

Hot cabinets, insulated, aluminum & stainless steel

Furnished with HE-2000 heating unit with 20 amps cord & NEMA 5-20P plug. 5" casters are standard. Power Requirements: Total 2075 watts on 110-120 volts. 60 hz, Single Phase, A.C.

CATALOG PAGES C-5 & C-6

Aluminum Hot Insulated Cabinets (Removable Racks) (see notes 1 & 2)

Table with columns: Type, Model Number, Pan Size, Pan Spacing, Pan Capacity, O.A. Dimensions (W, D, H), Weight, List Price. Rows include Extruded Side Channels and Angle Ledge models.



9252-HIN-DD-1834 (with optional push handles)

Stainless Steel Hot Insulated Cabinets (Removable Racks) (see notes 1 & 2)

Table with columns: Type, Model Number, Pan Size, Pan Spacing, Pan Capacity, O.A. Dimensions (W, D, H), Weight, List Price. Rows include Channel Slide and Angle Ledge models.

\*Dutch doors are standard on these 72 1/2" tall hot insulated cabinets. These are also available with single door. Deduct \$ 102 and delete "-DD" in the model number.

NOTE 1. These hot insulated cabinets are also available as "proof" only cabinets at no extra charge. Replace the letters "HIN" in the model number by letters "PIN". For hot/proof combination cabinets, see page PC-5. For other options, see, Table CC-1. Angle ledge cabinets are also available with spacing other than 3". Consult factory.

NOTE 2. Hot insulated cabinets can also be furnished with 1600w heating unit (HE-1600) for 15 amps service instead of standard 2000w heating unit (HE-2000) at no extra charge. Consult factory.