



Deluxe, universal angle type heater/proofer combination cabinets, insulated & non-insulated

Furnished with HPR-2000 heating/proofering unit with 20 amps cord & NEMA 5-20P plug. 5" casters are standard.
Power Requirements: Total 2075 watts on 110-120 volts.
60 hz, Single Phase, A.C.

CATALOG PAGE C-4

Deluxe Aluminum Hot/Proof Cabinets (Universal Angle Slide Type)

Type	Model Number	Pan Size (Inches)	Pan Capacity	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)	List Price (see note 3)
					W	D	H		
Non-Insulated	9231-HP-UA-17	Note 2	17 (Note 1)	3	29½	33¾	71	245	\$3,508
Insulated	9234-HP-IN-UA-17	Note 2	17 (Note 1)	3	31½	36¾	72½	305	P.O.R.



9231-HP-UA-17

Deluxe Stainless Steel Hot/Proof Cabinets (Universal Angle Slide Type)

Type	Model Number	Pan Size (Inches)	Pan Capacity	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)	List Price (See note 3)
					W	D	H		
Non-Insulated	2231-HP-UA-17	Note 2	17 (Note 1)	3	29½	33¾	71	292	\$5,983
Insulated	2234-HP-IN-UA-17	Note 2	17 (Note 1)	3	31½	36¾	72½	378	P.O.R.

NOTE 1: Capacity shown is based on 3" spacing. Each unit is furnished with 17 sets of slides which are adjustable on 1½" centers.

NOTE 2: Each pair of slides can accommodate one (1) 18"x 26" bun pan or one (1) GN2/1 gastronorm pan or two (2) 14"x 18" trays or one (1) 23"x 23" screen or two (2) 12"x 20" steam pans or two (2) gastronorm GN1/1 pans.

NOTE 3: LEXAN® glass door is standard on 9231, 9234, 2231 & 2234 model series cabinets. Solid door in lieu of LEXAN® door is available at no extra charge for correctional or heavy institutional use. These cabinets are also available in half size (8 pan capacity) as well as in under counter sizes. Consult factory. For options, see Table CC-1

Hot/proof combination universal angle slide cabinets, insulated & non-insulated

Furnished with HPR-2000 heating/proofering unit with 20 amps cord & NEMA 5-20P plug. 5" casters are standard.
Power Requirements: Total 2075 watts on 110-120 volts.
60 hz, Single Phase, A.C.

CATALOG PAGES C-7A & C-8A

Aluminum Hot/Proof Combination Cabinets with Universal Angle Slides

Type	Model Number (Also see note 3)	Tray Capacity (Note 1 & 2)	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)	List Price
				W	D	H		
Non-Insulated	9233-HP-UA-9	9	4½	26	31	59½	160	\$4,027
	9233-HP-UA-10	10	4½	26	31	65½	170	4,275
	9233-HP-UA-11	11	4½	26	31	70	185	4,368
Insulated	9235-HP-IN-UA-9	9	4½	29½	36¾	60½	265	4,476
	*9235-HP-IN-DD-UA-12	12	4½	29½	36¾	72½	295	5,116



9235-HP-IN-DD-UA-12

Stainless Steel Hot/Proof Combination Cabinets with Universal Angle Slides

Type	Model Number (Also see note 3)	Tray Capacity (Note 1 & 2)	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)	List Price
				W	D	H		
Non-Insulated	2233-HP-UA-9	9	4½	26	31	59½	252	P.O.R.
	2233-HP-UA-11	11	4½	26	31	70	280	\$6,147
	2235-HP-IN-UA-9	9	4½	29½	36¾	60½	378	6,980
Insulated	2235-HP-IN-UA-12	12	4½	29½	36¾	72½	402	7,552
	*2235-HP-IN-DD-UA-12	12	4½	29½	36¾	72½	410	7,794

*Furnished with dutch doors as standard on this model.

NOTE 1: Tray capacity is shown for 18"x 26" bun pans. Capacity for 12"x 20" steam pans/gastronorm (GN1/1) pans (2½" or 4" high) or 14"x 18" trays is twice the number.

NOTE 2: Slides are adjustable on 1½" centers. Each universal slide set can carry one (1) 18"x 26" bun pan or 20"x 20" baking pan or gastronorm (GN2/1) pan or 20"x 20" glass rack or two (2) 12"x 20" steam pans or gastronorm (GN1/1) pan or 14"x 18" trays.

NOTE 3: Solid door is standard on these 9233, 9235, 2233 & 2235 model series cabinets. Optional LEXAN® glass door is available. For options, see Table CC-1.



TABLE CC-1
OPTIONS FOR PROOFER & HOT CABINETS

Table with 3 columns: Item Description, ALUMINUM MODELS, and STAINLESS STEEL MODEL. It lists 31 options for proofer and hot cabinets, including bumpers, casters, locks, and heating units, with corresponding prices for aluminum and stainless steel models.

*FOR HOT INSULATED CABINETS WITH TOP MOUNTED HEATING UNITS ONLY.

NOTE: Most aluminum hot, proof & hot/proof cabinets are also available in s/s construction. Add 65% to list prices of aluminum models unless listed otherwise based on a minimum quantity of 5 units & an up charge of 20% to 80% may apply for quantities under 5. Consult factory.